

XIAMEN FREEDE INDUSTRY CO.,LTD.

Add:NO 58 Building, Yuemeijia Park, Jimei District, XIAMEN CHINA 361022 TEL: +86-0592-8628902 FAX: +86-592-6065010 www.cablecutting.net

Wire splicing machine WPM-TDJ04



Available coverage:

A.connecting of wire and neon light

B.connecting of the LED resistance

C.connecting of swithc and lead

D.connecting of head of the transformers

E.connecting of resistance and the wire

F.connecting of the constant-temperature fuse.

This machine is a new type of connecting equipment, that adopt packaging connecting to replace the normal solder connecting or hand riveting, which will be more convenient and dependable, also it doesn't have the disadvantages of air pollution that cool welding and air welding brings, so as to pass the UL, JIS security tests.

It used for successive copper terminal, cutting , forming and pressing at the same time. High efficiency, low cost, and no waste. $\frac{1}{2} \left(\frac{1}{2} \right) = \frac{1}{2} \left(\frac{1}{2} \right) \left(\frac{$

After connecting, the riveting capability of the copper terminal is stable and firm.

It is also equipped with the straight and curl mould set for connecting different products.

Dimesion: 340×370×410(MM)

Weight: 55KG Ram Travel :23MM

Range copper strip width:2MM/4MM/6MM

Nominal pressure:10KN

Production efficiency 200Pcs/MIN Power: AC220V 50HZ/180W





